

Adsorption of phenol from aqueous solution on to *Luffa Cylindrica* Cords: equilibrium, kinetic, and thermodynamic study

Y. Laidani^{1*}, G. Henini², S. Hanini³, A. Fekaouni¹

¹Laboratory Chemical Plant - Water – Energy, Department of chemistry
Chlef University, P.O. Box 151, Hay Essalem, 02000 Chlef, Algeria

*Corresponding author: l.ykhlef@gmail.com; Tel.: +213 6 98 61 11 48

ARTICLE INFO

Article History :

Received : 25/07/2020
Accepted : 19/01/2021

Key Words:

Adsorption, phenol;
Kinetic;
thermodynamics;
biomass.

ABSTRACT/RESUME

Abstract: The results obtained show that *Luffa cylindrica* cords / phenol have an adsorption capacity ($q_m=2.54$ mg/g). The adsorption process was rapid and reached equilibrium in 25 min of contact at 23 °C and pH 8.5. The different adsorption models Langmuir, Freundlich, Temkin and Elovich were used for the mathematical description of the adsorption equilibrium, and it was found that the very well - equipped experimental data for the Langmuir model ($R^2=0.994$), the pseudo - first - order and pseudo - second - order kinetic models were applied to the experimental data. The experimental data fitted very well the pseudo-second-order kinetic model ($R^2= 0.999$) and also followed the model of intra particle diffusion (K_{dif} vary from 0.125 to 0.374 mg/g.min^{1/2} for concentrations between 10 and 100 mg/L), whereas diffusion is not the only rate - control step. Finally the thermodynamic constants of adsorption phenomena, ΔH° and ΔS° were found to be - 6.219 kJ/mol and -0.019 kJ/mol.K in the range of 3 – 23 °C respectively. The negative value of the Gibbs free energy ΔG° demonstrates the spontaneous nature of phenol adsorption onto *Luffa cylindrica* cords.

I. Introduction

Heavy metal pollution is an environmental problem of worldwide concern. The heavy metals are among the most common pollutants found in industrial effluents [1]. Chrome is one of toxic heavy metals and it can be present in wastewater from electroplating, refining and welding industries [2]. The chronic toxicity of chrome to humans and the environment has been well documented and high concentration of chrome causes cancer of lungs, nose and bone [3]. Several processes have been employed for the removal of chrome ions from water and wastewater including chemical precipitation, ion-exchange, membrane filtration, electrochemical treatment and adsorption [4].

Wastewaters containing phenolic compounds are a serious environmental problem, and these waters cannot simply be released into the environment without treatment.

The discharge of wastewater containing large amounts of organic contaminants represents a serious risk to the general population [1].

Wastewater containing organic contaminants such as phenolic compounds implies serious discharge problems, due to their poor biodegradability, high toxicity, and possible accumulation in the environment [2]. Phenols are introduced into surface water from industrial effluents, such as those from plastic, leather, paint, rubber, pharmaceuticals, petrochemicals, and pesticides, among others [3-5]. It is a fact that phenol and its derivatives found in natural water sources represent a serious risk to human health and water quality [6]. Phenolic compounds represent a serious danger because of their high toxicity and carcinogenicity even at low concentrations. In some industries such as food processing, the rejected effluents may contain relatively large amounts of substances (phenolic) so that the aquatic environment is constantly threatened [7]. Indeed, in normal activity, a single refinery can reject up to 0.5 mg/L of phenol while a catalytic cracking unit of oil can reject up to 1 mg/L. the maximal concentration

phenol in water for consumption is 0.001 mg/L in the European standard [7].

Various techniques have been used for phenol removal in the wastewater treatment. In general, these removal techniques are divided into three main categories: physical, chemical and biological [8]. Traditionally, biological treatment, adsorption, reverse osmosis, ion exchange, catalytic oxidation and solvent extraction are the most widely used techniques for removing phenol and related organic substances [8, 9]. Among all of these methods adsorption has been preferred due to its cheapness and the high-quality of the treated effluents especially for well-designed sorption processes [10]. Adsorption by agricultural by-products used recently as an economical and realistic method for removal of different pollutants has proved to be efficient at removing of phenol [11, 12]. *Luffa cylindrica* cords (LCC), mainly consists of cellulose, hemicelluloses and lignin; of composition (60%, 30% and 10% by weight, respectively) [13]. Cellulose structure consists of monomeric unit of a β - D - glucopyranose linked through 1,4-glucosidic linkage. Cellulose is renewable, cheap and low in density, exhibits better processing flexibility and is a biodegradable material. Cellulose is a highly functionalized, linear stiff chain homopolymer, characterized by its hydrophilicity, chirality, biodegradability and broad chemical modifying capacity [14]. Because of its unique structure, *Luffa cylindrica*, has been used as an efficient adsorbent or as a carrier for immobilization of some microalgal cells for the removal of water pollutants [15, 16]. For the present study, a batch - contact - time method was used, and the equilibrium of phenol adsorption onto *Luffa cylindrica* cords were investigated with the attempts to fit the data to Langmuir, Freundlich, Temkin and Elovich equations. The uptake of phenol on *Luffa cylindrica* cords were examined as a function of temperature, initial phenol concentration, adsorbent dose, pH, and contact time. The adsorption kinetic data of the biomaterial were tested by the pseudo - first - order and the pseudo - second - order kinetic models. The thermodynamics of the adsorption was also evaluated.

II. Materials and methods

II.1. Preparation of biosorbent

The vegetable sponge of *Luffa cylindrica* cords (LCC) is an natural product which grows in the north of Algeria. The pre-treatment of the sponges consisted of cooking with boiling water for 30 min followed by washing with distilled water in order to remove the seeds and loose cord fragments.

These cords were then placed in a solution of NaOH (12%) for 15 min and washed again with tap water. They are whitened with bleach 12% for 3 h at ambient temperature after which the cords are rinsed. At pH >8.5, the decrease of phenol adsorption may have resulted from the following reasons. Similar

with distilled water several times. The cords of LCC were oven dried at 105 °C for 120 min, then crushed and sifted by standard sifting and crushing.

II.2. Preparation of solution

Phenol used in this study was obtained from Shanghai Chemical Co., Ltd. (analytical grade). Stock solution was prepared by weighing out the pure crystalline solid in solution of sodium bicarbonate 0.1 N for phenol. The test solutions were prepared by diluting some stock solution up to the desired concentration. The ranges of concentrations of phenol prepared from stock solution varied between the values of 10 and 100 mg/L. The pH of each solution was adjusted to the required value pH = 8.5 with the 0.1 N sodium bicarbonate.

II.3. Methods of adsorption studies

Batch adsorption studies were conducted by shaking the flasks for a period of time using an air bath mechanical shaker. The experimental process was as followings: put a certain quantity of LCC into conical flasks, then, added the phenol solution in single component system, vibrated sometime at a constant speed of 350 rpm in a shaking air bath. After a period of shaking and contact time, took out the conical flasks, filtrated to separate LCC powders and the solution. The phenol concentration analysis of filtrate solution was immediately measured with UV-visible spectrophotometer ((Unicam 8625, France)) at 270 nm wavelength. The phenol adsorption capacity (q_e , mg/g) was determined as follows:

$$q_t = \frac{(C_0 - C_t) V}{m} \quad (1)$$

Where q_t is the amount of phenol taken up by the adsorbent (mg/g); C_t (mg/L) is the concentration of phenol solution at time, t (min), C_0 (mg/L) is the initial concentration of phenol. V and m are the volume of the solution (L) and the mass of the adsorbent (g), respectively.

III. Results and discussion

III.1. Effect of pH on the removal of phenol

The effect of solution pH in the range from 2 to 12 on phenol adsorption is shown in Figure 1. As seen, the removal decreased from about 78% to 58% when pH decreased from 2 to 12. The removal of phenol by LCC was highly dependent on pH.

The phenol removal increases with pH from 2.0 to 8.5, then sharply decreases at pH >8.5. The maximum adsorption is attained at pH of 8.5. At pH 2.0, there are many positive charges on the surface of LCC, which give a large static repulsion force. As pH increases from 2.0 to 8.5 the static repulsion force decreases and the phenol adsorption increases.

results have been reported by other groups such as Abdelwahab et al. [12] and Nadavala et al. [17].




Figure 1. Effect of pH on the adsorption of phenol onto LCC ($m = 1$ g, $V = 300$ ml, $T = 23$ °C)

III.2. Effect of adsorbent dose

These experiments gave the effect of solid/liquid ratio on the adsorption efficiency at equilibrium (Figure 2). The results demonstrated, for the selected sawdust and in presence of 100 mg/L of initial phenol concentration that the phenol adsorption capacity did not change significantly for a solid/liquid ratio higher than 3.33 g/L. In fact, the adsorption capacity obtained with 0.82 g/L of solid/liquid ratio was 0.82 mg/g; however, for 1.7, 2.5 and 3.33 g/L respectively. Similar results were previously reported by some researchers [18].




Figure 2. Effect of adsorbent dosage on the phenol adsorption onto LCC: $V = 300$ ml, $T = 23$ °C,

III.3. Effect of contact time on phenol adsorption

The results obtained from the Adsorption rate tests are shown in Figure 3, the evolution of the adsorbed quantity of phenol per gram of LCC as a function of the contact time at initial concentration 100 mg/L as a phenol, showing that the amount of adsorbate fixed on each material increases with the increase of the content of the solution in phenol.




Figure 3. Effect of Contact time on phenol removal onto LCC: pH 8.5, $m = 1$ g.

A rapid adsorption is observed at the beginning and then a spreading with saturation. A rapid increase in the adsorption capacity of the phenol occurs within a few minutes (12 min), due to the adsorption of phenol to the surface of the particles of each adsorbent. This first phase constitutes the essential part of the phenomenon of adsorption because the kinetics of fixation is limited by the low residual concentration of phenol. In the second stage, the occupation of deep adsorption sites requires diffusion of the adsorbate within the micropores of the adsorbent. Similar results have been reported by other groups such as Cherifi et al. [19] and Afsharnia et al. [20].

III.4. Effect of temperature

The temperature is well known to play an important role in the adsorption process [21]. The adsorption capacity for the system (Phenol / LCC) increases with increasing the temperature from 4 to 23 °C. The best removal efficiency (2.54 mg/g and 84%) was obtained at a temperature of 23 °C (Figure 4). Similar of the adsorption process has been reported for other adsorbent systems [7, 11, 22].




Figure 4. Effect of temperature on the amount adsorbed by the LCC / phenol pH 8.5.

III.5. Adsorption Equilibrium Study

Adsorption isotherms describe the theoretical adsorption maximum capacity of quantitative adsorbents, and determined the feasibility of adsorbent dosage; however, they serve as important reference values in the design process of the adsorption system.

In this study, the adsorption isotherms were plotted using the Langmuir, Freundlich, Temkin and Elovich model [23]. The Langmuir isotherm assumes monolayer adsorption onto a surface containing a finite number of adsorption sites, using uniform strategies of adsorption [24]. The linear form of the Langmuir isotherm equation is given as:

$$\frac{C_e}{q_e} = \frac{1}{K_L q_m} + \frac{C_e}{q_m} \quad (2)$$

Where C_e is the equilibrium concentration of the adsorbate (mg/L), q_e is the sorption capacity of adsorbent at equilibrium (mg/g), q_m and K_L are the maximum phenol adsorbed per unit mass of the adsorbent (mg/g) and Langmuir constant, in relation to energy of sorption which quantitatively indicates the affinity between the adsorbent and phenol (L/mg), respectively [25].

The favorable or unfavorable of the adsorption system can be determined based on the essential characteristic of the Langmuir model which can be expressed in terms of a dimensionless constant separation factor or equilibrium parameter, R_L , which is defined as follows :

$$R_L = \frac{1}{1 + K_L C_0} \quad (3)$$

The value of R_L indicates the shape of isotherm to be either unfavorable ($R_L > 1$), linear ($R_L = 1$), favorable ($0 < R_L < 1$) or irreversible ($R_L = 0$) [26]. The Freundlich equation can be linearized in a logarithmic form for the determination of the Freundlich constants as follows [27] :

$$\ln(q_e) = \ln(k_F) + \frac{1}{n_F} \ln(C_e) \quad (5)$$

Where K_F (mg^{1+1/n}/g. L^{1/n}) and $1/n_F$ are the adsorption constants of Freundlich model generally related to the strength of interaction between adsorbate and sorbent. They can be determined from the plot of $\ln(q_e)$ vs $\ln(C_e)$ [28, 29].

Temkin's model rests on the assumption that during the adsorption gas phase, the heat of adsorption due to interactions with the adsorbate decreases linearly with the recovery rate θ . From q_e plotted as a function of $\ln C_e$, B_T , and K_T values can be determined [30]:

$$q_e = \frac{RT}{B_T} \ln(K_T \cdot C_e) \quad (6)$$

Where R is the perfect gas constant (8.314 J/mol.K), T is the absolute temperature (°C), B_T is the variation in energy of adsorption (J/mol), and K_T is the constant of Temkin (L/mg).

Elovich equation is also used successfully to describe second order kinetic assuming that the actual solid surfaces are energetically heterogeneous, but the equation does not propose any definite mechanism for adsorbate-adsorbent [31]. It has extensively been accepted that the

chemisorption process can be described by this semi-empirical equation [32]. The linear form of this equation is given by [31] :

$$q_t = \frac{1}{\beta_{El}} \ln(\alpha_{El} \beta_{El}) + \frac{1}{\beta_{El}} \ln(t) \quad (7)$$

Where α_{El} is the initial adsorption rate (mg /g.min), and the parameter β_{El} is related to the extent of surface coverage and activation energy for chemisorption (g/mg). The Elovich coefficients could be computed from the plots q_t vs $\ln(t)$. The initial adsorption rate, and the desorption constant, β_{El} , were calculated from the intercept and slope of the straight-line plots of q_t against $\ln(t)$.

The plots of C_e/q_e vs. C_e for the adsorption of phenol at 4, 17, and 23 °C according to the linear form of the Langmuir isotherm is shown in Figure 5. Table 1 summarizes the constants of the Langmuir, Freundlich, Elovich and Temkin isotherms obtained from the slope and the interception of the plots of each isotherm at different temperatures. The values of R^2 exceed 0.9 for the two models of Langmuir and Freundlich, suggesting that the two models with near experimental results.




Figure 5. Linearization of the Langmuir equation for adsorbing phenol / LCC

Figure 5 shows the Langmuir plot for the adsorption of phenol onto LCC at 4, 17 and 23 °C, as reproduced by the linearized Langmuir (2), and the best straight lines representing the fitted points. Hence, it is evident that the equilibrium data are accommodated well by the Langmuir model, with high correlation coefficients, as shown in Table 1. Such coefficients are indicative of monolayer coverage of the phenol at the outer surface of the LCC particles, and with maximum adsorption capacity (Table 1). The results of Table 1 also show that an increase in temperature from 4 to 23 °C promoted an increase in the adsorption capacity.

Similar results were found for the adsorption of phenol onto *Luffa cylindrica* cords shells [22].

Table 1. Parameters of different adsorption models for phenol / LCC

Isotherm model	Parameter	Temperature (°C)		
		4	17	23
Freundlich	K_F ($\text{mg}^{1+1/n}/\text{g} \cdot \text{L}^{1/n}$)	0.180	0.298	0.518
	$1/n_F$	0.081	0.084	0.092
	R^2	0.960	0.966	0.95
Langmuir	q_m (mg/g)	0.236	0.368	0.710
	K_L (L/g)	1.35	1.25	1.12
	R^2	0.996	0.997	0.990
	R_L	0.007	0.008	0.009
Temkin	K_T (L/g)	1159.16	1063.151	41115.216
	B_T (J/mol)	1072.774	1095.643	1567.393
	R^2	0.450	0.451	0.452
Elovich	α_{Ei} (mg/min.g)	536.932	365.669	5828
	β_{Ei} ([g/mg])	34.83	9.709	6.849
	R^2	0.547	0.458	0.765

According to the R_L values, all the systems correspond to favorable adsorption processes (Table 1). The values tended toward zero, representing the ideal irreversible case, rather than toward unity, representing the completely reversible case [33].

By comparison of the results obtained in this study with those in the previously reported works (Table 2) on adsorption capacities of various low-cost adsorbent in aqueous solution for Phenol, it can be stated that our findings are extremely good.

Table 1. Previously reported adsorption capacities of various adsorbents for phenol

Adsorbents	q (mg/g)	Ref.
Raw Moroccan Pyrophyllite	11,22	[34]
Luffa cylindrica fibers	0.97	[12]
Granular activated carbon	213	[35]
Organic-inorganic hybrid mesoporous material	11	[36]
Water hyacinth ash	6.4	[37]
FCM (Fibers gourds Mexicain)	0.69	[11]
Date stones	48.71	[38]
Sugarcane bagasse fly ash	23.832	[39]
Luffa cylindrica cords	2.54	This study

II.6. Adsorption Kinetics

Pseudo - first - order kinetic model was set forth by Lagergren in 1898 [40]. This model is not applicable for a total adsorption period for many instances. It can be generally used for the first minutes of adsorption procedure in other words for the periods before reaching equilibrium. This adsorption rate can be expressed by the equation.

$$\frac{dq}{dt} = k_1 (q_e - q_t) \quad (8)$$

The integrated form of the Lagergren equation is given by:

$$\text{Log}(q_e - q_t) = \text{Log} q_e - \frac{k_1}{2.303} t \quad (9)$$

Where q_e and q_t are the amounts adsorbed at equilibrium and at time, t (mg/g), and k_1 is the rate

constant of the pseudo - first - order adsorption (min^{-1}).

The pseudo-second-order kinetic model (10) is another model used in the analysis of adsorption kinetic data. Contrary to the pseudofirstorder kinetic model, this model is compatible with the mechanism of rate-controlling step throughout the adsorption. The pseudo - second-order kinetic model is given by the following equation [41]:

$$\frac{t}{q_t} = \frac{1}{k_2 q_e^2} + \frac{1}{q_e} t \quad (10)$$

Where k_2 is the rate constant of the pseudo-second order adsorption ($\text{g}/\text{mg} \cdot \text{min}^{-1}$).

The kinetics of adsorption of the adsorbate on the adsorbent was verified at different initial concentrations (10, 60 and 100 mg/L).

The validity of each model was determined by the sum of squared errors (SSE), given by :

$$SSE = \frac{1}{N} \sqrt{\sum (q_{e,exp} - q_{e,cal})^2} \quad (11)$$

where N is the number of trials. Low value indicates a better SSE smoothing.

The intraparticle diffusion parameter, k_{dif} , is defined by the following equation [42]:

$$q_t = K_{dif} t^{1/2} + C \quad (12)$$

Where k_{dif} is the intraparticle diffusion constant (mg/g.min^{1/2}), and c is the intercept. The intraparticle diffusion plots of the experimental results, qt versus t^{1/2} for different initial phenol concentrations at 23 °C.

The kinetic parameters for adsorption of phenol presented in Table 3 were calculated from plots of log (q_e-q_t) vs. t and the plots of t/q_t vs. t.

Table 3. Pseudo - first - order and Pseudo - second - order kinetic parameters for the adsorption of phenol onto LCC.

Kinetic model	Phenol (mg/L)	10	60	100
Pseudo - first - order kinetic model	q _{e, exp} (mg/g)	0.65	1.35	2.54
	q _{e, cal} (mg/g)	0.521	0.524	0.188
	K ₁ (min ⁻¹)	0.051	0.046	0.053
	R ²	0.601	0.881	0.681
	SSE (%)	4.62	27.53	78.40
Pseudo - second - order kinetic model	q _{e, cal} (mg/g)	0.855	1.383	2.564
	K ₂ (g/mg.min)	1.375	0.352	0.364
	R ²	0.999	0.999	0.999
	SSE (%)	6.83	1.10	0.80
Intraparticle diffusion	K _{dif} (mg/g.min)	0.125	0.203	0.374
	C (mg/g)	0.109	0.113	0.307
	R ²	0.978	0.918	0.871

For the first - order kinetic model, the obtained R² values were relatively low, ranging from 0.601 to 0.881, and the calculated q_{e(cal)} were much larger than the experimental q_{e(exp)}. The pseudo - second - order rate constant k₂ and the corresponding linear regression correlation coefficient values, R², are given in Table 3. The applicability of the kinetic model is compared by judging the correlation coefficients R² and the agreement between the calculated and the experimental q_e values. In a view of these both considerations, we may conclude that the pseudo second-order mechanism is predominant R² (0.999). Similar results have been reported by other groups such as Uddin et al. [37] and Kayode et al. [43].

We observe that the diffusion rate constants increase in the same direction as the initial concentration of phenol Table 3. Indeed for initial concentrations between 10, 60 and 100 mg/L, the values of K_{dif} vary from 0.125 to 0.374 mg/(g.min^{1/2}) for the Phenol / LCC system. According to the study of Gundogdu et al. [44] on the diffusion intraparticle for the Phenol / Low-Cost Activated Carbon system, the value of K_{dif} is equal 0.5657 mg/(g min^{1/2}). So we note that the coefficient K_{dif} (0.374 mg/g.min^{1/2}) is 1.52 times greater than that of K_{dif}, found by Gundogdu et al. [44] to the concentration C₀ = 100 mg/L.

II.7. Adsorption thermodynamics

Figure 9 shows just such a plot with a correlation coefficient of 0.720 (Table 4). The ΔH⁰ and ΔS⁰ values are thus found to be - 6.219 kJ/mol and - 0.019

The influence of adsorption temperature (4 to 23 °C) on the adsorption of phenol was investigated. It can be observed that the adsorption of phenol decreases with increasing temperature. This probably indicates a poor chemical reaction interplay between adsorbate and surface functionalities of LCC [45]. Thermodynamic parameters such as free energy change (ΔG⁰), enthalpy (ΔH⁰), and entropy (ΔS⁰) were estimated according to the following equations [46] :

$$\Delta G^0 = -RT \ln(k_L) \quad (13)$$

$$\Delta G^0 = \Delta H^0 - T\Delta S^0 \quad (14)$$

A convenient form of the Van't Hoff equation then relates K_L to the standard enthalpy and entropy changes of adsorption, ΔH⁰ and ΔS⁰, respectively [47] :

(13) can be written as :

$$\ln(k_L) = \frac{\Delta S^0}{R} - \frac{\Delta H^0}{R} \cdot \left(\frac{1}{T}\right) = - \frac{\Delta G^0}{R} \cdot \frac{1}{T} \quad (14)$$

Where K_L is the adsorption equilibrium constant, R is the gas constant (8.314 J/ mol.K), T is the temperature (°C). The values of ΔH⁰ and ΔS⁰ were obtained from the slope and the intercept of plot of Ln(K_L) versus 1/T for initial phenol concentrations of 10, 60 and 100 mg/L.

kJ/mol.°C, respectively, while the ΔG⁰ values are - 0.337, - 0.457, and - 0.715 kJ/mol. The negative ΔG⁰ values indicate the feasibility and spontaneous

nature of the adsorption process with a high preference of phenol on LCC [48].

The ΔH^0 for phenol adsorbed onto LCC was negative (-6.129 kJ/mol), indicating that the adsorption was exothermic. The ΔS^0 for phenol adsorbed onto LCC was -0.019 kJ/mol.°C The negative value of ΔS^0 suggested decrease in degree of freedom of the adsorbed phenol [49].

Adsorption processes with ΔG^0 values in the -20 to 0 kJ/mol range correspond to spontaneous physical processes, while those with values in the -80 to -400 kJ/mol range correspond to chemisorption [50].

As ΔG^0 changed from -0.337 to -0.715 kJ/mol when the temperature increased from 4, 17, and 23 °C, it can be concluded that the adsorption mechanism is dominated by physisorption, in keeping with the finding that the adsorption is rapid and more spontaneous at higher temperature. Spontaneous adsorption processes are a common feature of many other studies of this sort [51].

Similar results were reported in the literature for the adsorption of phenol by organomontmorillonit [52], the adsorption of phenol onto chemically modified activated carbon [53] and adsorption of phenol onto *Luffa cylindrica* fibers [12].




Figure 9. Relationship between Langmuir sorption equilibrium constant and temperature for phenol / LCC; $C_0=100$ mg/L.

Table 4. Thermodynamic parameters for the adsorption of phenol onto LCC different temperatures

T (°C)	ΔG^0 (kJ/mol)	ΔH^0 (kJ/mol)	ΔS^0 (J/mol.K)	R^2
4	-0.715			
17	-0.457	-6.219	-0.019	0.720
23	-0.337			

III. Conclusions

Kinetic, Equilibrium, and thermodynamic studies were made for the adsorption of phenol from aqueous solution onto LCC powder at pH 8.5. Results of adsorption showed that LCC can be effectively used as a biosorbent for the removal of

phenol. The kinetics studies of Phenol on LCC indicated that the adsorption kinetics of phenol on LCC followed the pseudo - second - order at different concentration values. The equilibrium data have been analyzed. The results showed that the phenol followed Langmuir isotherm. Thermodynamic studies indicated that the phenol adsorption onto LCC was a spontaneous, exothermic, and physical reaction. Based on the data of present study, LCC, an inexpensive and easily available material, can be an alternative for costlier adsorbents used for phenol removal in wastewater treatment processes.

IV. References

- Khemmari, F.; Benrachedi, K. A comparative study of raw and treated peach stones for the adsorption of hexavalent chromium: characterization, kinetic and thermodynamic modelling. *Algerian Journal of Environmental Science and Technology* 4 (2) (2018) 762-770.
- Khenniche, L.; Benissad-Aissani, F. Adsorptive Removal of Phenol by Coffee Residue Activated Carbon and Commercial Activated Carbon: Equilibrium, Kinetics, and Thermodynamics. *Journal Chemical Engineering Data* 55 (2010) 4677-4686.
- Lin, S.-H.; Juang, R.-S. Adsorption of phenol and its derivatives from water using synthetic resins and low-cost natural adsorbents. a review, *Journal of Environmental Management* 90(3) (2009) 1336-1349.
- Lazo-Cannata, J.C.; Nieto-Marquez, A.; Jacobyetal, A.. Adsorption of phenol and nitrophenols by carbon nanospheres: effect of pH and ionic strength. *Separation and Purification Technology* 80(2) (2011) 217-224.
- Yahia cherif, L.; Aissani-Benissad, F. Adsorption of phenol onto activated carbon prepared from coffee extract residue chemically activated using $ZnCl_2$. *Algerian Journal of Environmental Science and Technology* 2(1) (2016) 22-32.
- Mohd-Din, A. T.; Hameed, B.H. ; Ahmad, A.L. Batch adsorption of phenol onto physiochemical-activated coconut shell. *Journal of Hazardous Materials*. 161(2-3), (2009) 1522-1529.
- Desmiarti, R.; Trianda, Y.; Martynis, M. ; Viqri, A.; Yamada, T.; Li, F. Phenol adsorption in water by granular activated carbon from coconut shell. *International Journal of Technology*. 10(8) (2019). 1488-1497.
- Dursun, G.; Çiçek, H.; Dursun, A.Y. Adsorption of phenol from aqueous solution by using carbonised beet pulp. *Journal of Hazardous Materials B*125 (2005) 175-182.
- Ildefonso, B.N.; Jorge, S.A.; Angel, G.D.; Alvaro, R.J. Removal and Biodegradation of Phenol by the Freshwater Microalgae *Chlorella Vulgaris*. *Contemporary Engineering Sciences* 11(40) (2018) 1961 - 1970.
- Sonawane Bhausahab, K.; Korake, S.R. Removal of phenol from wastewater using low cost adsorbent. *International Journal of Science, Engineering and Technology Research* 5(6) (2016) 2249-2253.
- Henini, G.; Laidani, Y.; Souahi, F.; Hanini, S. Study of static adsorption system phenol / *Luffa cylindrica* fiber for industrial treatment of wastewater. *Energy Procedia* 18 (2012) 395-403.
- Abdelwahab, O.; Amin, N.K. Adsorption of phenol from aqueous solutions by *Luffa cylindrica* fibers: Kinetics, isotherm and thermodynamic studies. *Egyptian Journal of Aquatic Research* 39 (2013), 215-223.
- Laidani, Y.; Hanini, S.; Mortha, G.; Henini, G. Study of a Fibrous Annual Plant, *Luffa Cylindrica* for Ppaper Application Part I: Characterization of the Vegetal. *Iranian*

- Journal of Chemistry and Chemical Engineering* 31(4) (2012) 119-129.
14. Gupta, V.K.; Agarwal, S.; Singh, P.; Pathania, D. Acrylic acid grafted cellulosic Luffa cylindrical fiber for the removal of dye and metal ions. *Carbohydrate Polymers* 98 (2013) 1214-1221.
 15. Tanobe, V.O.A.; Sydenstricker, T.H.D., Munaro, M., Amico, S.C., "A comprehensive characterization of chemically treated Brazilian sponge-gourds (*Luffa cylindrica*) *Polym. Test.* 24 (2005) 474-482.
 16. Demir, H.; Top, A.; Balkose, D.; Ulku, S. Dye adsorption behaviour of Luffa cylindrical fibers. *Journal of Hazardous Materials* 153 (2008) 389-394.
 17. Nadavala, S.K.; Kim, M.N. Removal of phenolic compounds from aqueous solutions by biosorption onto acacia leucocephala bark powder: equilibrium and kinetic studies. *Journal Chilean Chemical Society* 56(1) (2011).
 18. Ma, Y.; Gao, N.; Chu, W.; Li, C. Removal of phenol by powdered activated carbon adsorption. *Frontiers of Environmental Science & Engineering* 7(2) (2013) 158-165.
 19. Cherifi, H.; Hanini, S.; Bentahar, F. Adsorption of phenol from wastewater using vegetal cords as a new adsorbent. *Desalination* 244 (2009) 177-187.
 20. Afsharnia, M.; Saeidi, M.; Zarei, A.; Reza, M.; Narooie, M.; Biglari, H. Phenol removal from aqueous environment by adsorption onto pomegranate peel carbon. *Electronic Physician* 8(11) (2016) 3248-3256.
 21. Aksu, Z.; Karabayir, G. Comparison of biosorption properties of different kinds of fungi for the removal of Gryfalan Black RL metal-complex dye. *Bioresource Technology* 9 (2008) 7730-7741.
 22. Hameed, B.H.; Rahman, A.A. Removal of phenol from aqueous solutions by adsorption onto activated carbon prepared from biomass material. *Journal of Hazardous Materials* 160 (2008) 576-581.
 23. Mohebbi, S.; Bastani, D.; Shayesteh, H. Methylene blue removal using modified celery (*Apium graveolens*) as a low-cost biosorbent in batch mode: Kinetic, equilibrium, and thermodynamic studies. *Journal Molecular. Structural* 1173 (2018) 541-551.
 24. Akpen, G. D.; Aho, M. I.; Mamwan, M.H. Equilibrium and Kinetics of Colour Adsorption from Textile Wastewater by a Novel Adsorbent. *Global Journal of Pure and Applied Sciences* 24 (2018) 61-67.
 25. Malakootian, M.; Askarpour, A.; Amirmahani, N.; Nasiri, Z.; Nasir, A. Removal of Hexavalent Chromium from Aqueous Solutions Using Magnetic Nanoparticles Coated with Alumina and Modified by Cetyl Trimethyl Ammonium Bromide. *Journal of Community Health Research* 4(3) (2015) 177-193.
 26. Dehvari, M.; Ehrampoush, M.; Ghaneian, H.; Taghi, M. Adsorption Kinetics and Equilibrium Studies of Reactive Red 198 Dye by Cuttlefish Bone Powder. *Iranian Journal of Chemistry and Chemical Engineering* 36(2) (2017) 143-151.
 27. Haq Nawaz, B.; Rubina, K.; Muhammad Asif, H. Biosorption of Pb (II) and Co (II) on Red Rose Waste Biomass. *Iranian Journal of Chemistry and Chemical Engineering* 30(4) (2011) 81-87.
 28. Beigi, S.M.; Babapoor, A.; Maghsoodi, V.; Mousavi, S.M.; Rajabi, N. Batch Equilibrium and Kinetics Studies of Cd (II) Ion Removal from Aqueous Solution Using Porous Chitosan Hydrogel Beads. *Iranian Journal of Chemistry and Chemical Engineering* 28(3) (2009) 81-89.
 29. Xu, H.; Liu, D.; He, L.; Liu, N.; Ning, G. Adsorption of Copper (II) from an Wastewater Effluent of Electroplating Industry by Poly (ethylenediamine) - Functionalized Silica. *Iranian Journal of Chemistry and Chemical Engineering* 34(2) (2015) 73-81.
 30. Seo-Hui, P.; Jin-Hyun, K. Isotherm, Kinetic, and Thermodynamic Characteristics for Adsorption of 2,5-Xylenol onto Activated Carbon. *Biotechnology and Bioprocess Engineering* 23 (2018) 541-549.
 31. Çiriğ Selçuk, N.; Kubilay, Ş.; Savran, A.; Rıza Kul, A. Kinetics and Thermodynamic Studies of Adsorption of Methylene Blue from Aqueous Solutions onto Paliurus spina-christi Mill. Frutis and Seeds. *OSR Journal of Applied Chemistry* 10(1) (2017) 53-63.
 32. Zhang, J.; Stanforth, R. Slow Adsorption Reaction between Arsenic Species and Goethite (α -FeOOH): Diffusion or Heterogeneous Surface Reaction Control. *Langmuir* 21(7) (2005) 2895-2901.
 33. Almeida, C.A.P.; Debacher, N.A.; Downsc, A.J.; Cottet, L.; Mello, C.A.D. Removal of Methylene Blue from Colored Effluents by Adsorption on Montmorillonite Clay. *Journal of Colloid and Interface Science* 332 (2009) 46-53.
 34. El Gaidoumi, A.; Chaouni Benabdallah, A.; Lahrichi, A.; Kherbeche, A. Adsorption of Phenol in Aqueous Medium by a Raw and Treated Moroccan Pyrophyllite. *Journal of Materials and Environmental Science* 6 (8) (2015) 2247-2259.
 35. Leong, KY.; Adnan, R.; Lim, PE.; Ng, SL.; Seng, CE. Effect of operational factors on bioregeneration of binary phenol and 4- chlorophenol-loaded granular activated carbon using PVA immobilized biomass cryogels. *Environmental Science Pollution Research* 24(26) (2017) 20959-20971.
 36. Makhlof, M.; Hamacha, R.; Villières, F.; Bengueddach, A. Kinetics and thermodynamics adsorption of phenolic compounds on organic-inorganic hybrid mesoporous material. *International Journal of Innovation and Applied Studies* 3(4) (2013) 1116-1124.
 37. Uddin, M.T.; Islam, M.S.; Abedin, M.Z. Adsorption of phenol from aqueous solution by water hyacinth ash. *Journal of Engineering and Applied Sciences* 2(2) (2007), 11-17.
 38. Dhidan, S.K. Removal of phenolic compounds from aqueous solutions by adsorption onto activated carbons prepared from date stones by chemical activation with FeCl₃. *Journal of engineering* 1(18) (2012) 63 - 77.
 39. Srivastava, V.C.; Swamy, M.M.; Mall, I.D.; Prasad, B.; Mishra, I.M. Adsorptive removal of phenol by bagasse fly ash and activated carbon: equilibrium, kinetics and thermodynamics. *Colloids Surface A: Physicochemical Engineering Aspects* 27 (2006) 289-104.
 40. Lagergren, S. Zur Theorie Der Sogenannten Adsorption Gelöster Stoffe, *Kungliga Svenska. Vetenskapsakademiens, 4th edition, Handlingar* Vol 24 (1898) 1-39.
 41. Elmouwahidi, A.; Bailón-García, E.; Pérez-Cadenas, A.F.; Maldonado-Hódar, F.J.; Carrasco-Marín, F. Activated carbons from KOH and H₃PO₄ activation of olive residues and its application as supercapacitor electrodes. *Electrochimic Acta*, 229 (2017) 219-228.
 42. Weber, J.R.; Morris, J.C. Kinetics of Adsorption on Carbon from Solution. *Journal of the Sanitary Engineering Division* 89(2) (1963) 31-60.
 43. Kayode, O. A.; Bamidele, I.O.; Emmanuel, C.C. Removal of Safranin-O from Aqueous Solution by Adsorption onto Kaolinite Clay. *Journal of Encapsulation and Adsorption Sciences* 4 (2014) 89-104.
 44. Gundogdu, A.; Duran, C.; Basri Senturk, H.; Soylak, M.; Ozdes, H.; Imamoglu, M. Adsorption of Phenol from Aqueous Solution on a Low-Cost Activated Carbon Produced from Tea Industry Waste: Equilibrium, Kinetic, and Thermodynamic Study. *Journal of Chemical and Engineering Data* 57 (2012) 2733-2743.
 45. Goto, M.; Hayashi, N.; Goto, S. Adsorption and desorption of phenol on anion-exchange resin and activated carbon. *Environmental Science Technology* 20 (1986) 463-467.
 46. Bouhamed, F.; Elouear, Z.; Bouzid, J. Adsorptive removal of copper(II) from aqueous solutions on activated carbon prepared from Tunisian date stones: Equilibrium, kinetics and thermodynamics. *Journal of the Taiwan Institute of Chemical Engineers* 43 (2012) 741-749.
 47. Seki, Y.; Yurdakoc, K. Adsorption of Promethazine Hydrochloride with KSF Montmorillonite. *Adsorption* 12(1) (2006) 90-100.
 48. Yuh-Shan, Ho.; Augustine, E.; Fomaja, O. Kinetics and Thermodynamics of Lead Ion Sorption on Palm Kernel Fibre from Aqueous Solution. *Process Biochemistry* 40 (2005) 3455-3461.

49. Senthil Kumar, P.; Gayathri, R. Adsorption of Pb^{2+} Ions from Aqueous Solutions onto Bael Tree Leaf Powder: Isotherms, Kinetics and Thermodynamics Study. *Journal of Engineering Science and Technology* 4(4) (2009) 381-399.
50. Henini, G.; Laidani, Y.; Souahi, F.; Labbaci, A.; Hanini, S. Equilibrium, Kinetic and Thermodynamic Studies of the Biosorption of Textile Dye (Yellow Bemacid) onto *Brahea edulis*. *International Journal of Materials and Textile Engineering*, 10(7) (2016) 931-937.
51. Alkan, M.; Demirbaş, Ö.; Celikcapa, S.; Doğan, M. Sorption of acid red 57 from aqueous solution onto sepiolite. *Journal of Hazardous Materials*, 116(1) (2004) 135-145.
52. Fu, Q.L.; Deng, Y.L.; Li, H.S.; Liu, J.; Hua, H.Q.; Chen, S.W.; Sa, T.M. Equilibrium, kinetic and thermodynamic studies on the adsorption of the toxins of *Bacillus thuringiensis* subsp. *kurstaki* by clay minerals. *Applied Surface Science* 255 (2009) 4551-4557.
53. Canizares, P.; Carmona, M.; Baraza, O.; Delgado, A.; Rodrigo, M.A. Adsorption equilibrium of phenol onto chemically modified activated carbon F400. *Journal of Hazardous Materials* 131 (2006) 243-248.

Please cite this Article as:

Laidani Y., Henini G., Hanini S., Fekaoui A., Adsorption of phenol from aqueous solution onto *Luffa Cylindrica* Cords: equilibrium, kinetic, and thermodynamic study. ***Algerian J. Env. Sc. Technology*, 8:3(2022) 2553-2561**